



15x Zoom Lens



4K Ultra HD



USB 3.0





Built-in Microphone Array

V2

4K Video Conference Camera

V2 is suitable for medium and large conference rooms. Bring 4K ultra-HD high-definition picture quality and smooth sound quality. Integrated design that is easy to deploy and designed for large screens. Offer you video conference experience of no matching.

Compatible with the following products:



15x Zoom Lens with 4k HD Experience

The V2 is equipped with high quality CMOS for smooth output of 4K ultra HD video quality. The 15x zoom lens enables the close-up of the characters in the room and the zooming of the scene. Easy panorama shooting by a 85°-wide-angle camera combined with a rotating gimbal .



Auto Focus, Let the Lens Automatically Find You

The V2 features intelligent settings and auto focus for smooth and accurate recognition of faces and clear entry for each participant. Add presets and Privacy protection to meet the needs of more conference scenarios.



One-piece Design, USB Plug and Play

The V2 features a folding stand that can be used to hang a large screen and complete deployment in one minute. With USB3.0 interface, dual stream output, the video screen is more high-definition smooth.



Dual-microphone Stereo Radio, Clearly Transfer Your Voice

The V2 has two built-in microphone arrays with a pickup distance up to 4 meters. The sound is clear and smooth, avoiding noise and echo interference. And the audio and video are perfectly synchronized for achieving face-to-face communication.



V2

Product Specifications

Camera, lens Parameters

Image Sensor: 1/2.5" high quality CMOS sensor
Effective Pixels: 851 million
Video signal:
4K (3840X2160) ; 1920X1080 ; 1280X720 ; 720X480 ; 640X360
Perspective Wide angle: 86.13° (D), 79.18° (H), 49.22° (V)
Digital zoom: 15X
Video compression format: H.264, H.265, MJPEG, YUV
Image stream: Dual stream output
Audio input interface: Built-in 2-way MIC, pickup distance 4 meters
Signal to noise ratio: >55dB
Audio compression format: AAC, MP3, G.711A
Audio and video interface:
USB3.0 (B type compatible with USB2.0), A-OUT

PTZ Parameter

Horizontal and pitch rotation: -170° ~ +170°, -15° ~ +15°
Horizontal and pitch control speed: 0.1 to 65 ° / sec, 0.1 to 35 ° / sec
Preset speed: Level: 65°/sec, pitch: 35°/sec
Number of presets: 2 remote controls can be set

System Requirements

Windows 7 and above
Mac OS X 10.7 or later
Google Chromebook version 29.0.1547.70, platform 4319.79.0
Android 4.4 and above

Other Parameters

Storage temperature, humidity: -10°C ~ +60°C, 20% ~ 95%
Working temperature, humidity: -10°C ~ +50°C, 20% ~ 80%

Packaging Material:

Camera host × 1
Remote control × 1
Power adapter × 1
USB3.0 cable × 1
Instruction Manual × 1
Terms of after-sales service × 1
Certificate of conformity × 1

Size (length X width X height)

350mmX130mmX129.3mm